

38413024

Manually operated Fuse combination switch FUSERBLOC BS88 250A 3P



Strong points

- Improved safety
- High breaking capacity
- Multi-use
- Simplified use

General characteristics

- For industrial fuses up to 1250 A.
- 2P, 3P or 4P available.
- Up to 690 VAC.
- Up to 100 kA.

Compliance with standards

- IEC 60947-3
- BS EN 60947-3
- IEC 60269-1
- IEC 60269-2

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/38413024>

FUSERBLOC BS 88 units with right front-side operation are manually-operated multipole fuse load break switches. They provide make and break on load and safety isolation and protection against overcurrent for any low voltage electrical circuit. This range is available in direct and external operation, in 2, 3 and 4 poles and up to 1250 A.

Technical Characteristics

Height [mm]	195
Width [mm]	490
Depth [mm]	146
Weight [kg]	3.75
Control operator	Direct : H12 / External : S2
Fuse size	B1-B3
Number of poles	3
Rated current [A]	250
Type	I-O-Test
Frame size	15

Classification

UNSPSC	39122233
ETIM Class	EC001040
IGCC	5291

Commerce

Description	Manually operated Fuse combination switch FUSERBLOC 250A 3 poles, 690Vac, B1-B3 BS fuses, switching position I-O-Test, frame size 15 , direct front handle, external front and right side operator, not included
Effective date	2001-11-13
Offer Life Cycle Code	40
Country of origin	FR

ETIM - Electrical characteristics

Max. rated operation voltage Ue AC [V]	690
Rated permanent current Iu [A]	250
Rated operation power at AC-23, 400 V [kW]	132
Conditioned rated short-circuit current Iq [kA]	80
Number of poles	3

ETIM - Mechanical characteristics

Cable entry	Top/bottom
Equipped with connectors	No
Suitable for floor mounting	Yes
Suitable for front mounting	Yes
Suitable for busbar mounting	No
Degree of protection (IP), front side	IP20

ETIM - Technical features

Version as main switch	Yes
------------------------	-----

Version as safety switch	Yes
Suitable for fuses	Shape B1-B3
With error protection	No
Type of electrical connection of main circuit	Bolt connection
Type of control element	Long rotary handle
Position control element	Front side
Motor drive optional	No
Motor drive integrated	No
Version as emergency stop installation	Yes

Logistics

GTIN/EAN	3596031601530
Customs number	8536309000
Price unit	PC
Weight of the packing unit [kg]	3.75
Length of the packing unit [m]	0.2
Width of the packing unit [m]	0.21
Depth of the packing unit [m]	0.35

Norms

Conformity to standards	IEC
-------------------------	-----